



AMAZONESSENTIALS®
carpet tiles



SIRIM
Certified to: GB/T 2755 : 2005
Certification No.: PC011916



SIRIM
Eco-LABEL
Low VOC
Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212


SKYLAR VIBRANT

Stainshield PP | Synth PVC Back™




ES22-08
MEADOW


Recommended Laying Patterns



Quarter Turn



Ashlar




Brick

Product Specification

Fibre	Stainshield PP
Construction	1/10" Tufted Loop Pile
Pile Weight	544g/m ² or 16oz/yd ²
Pile Height	3.0mm
Total Thickness	5.0mm
Backing	Synth PVC Back™

Standard Size







AMAZONESSENTIALS®
carpet tiles

SKYLAR


VIBRANT

Stainshield PP | Synth PVC Back™

PP



SKYLAR | VIBRANT



ES22-08
MEADOW

PRODUCT SPECIFICATION

CONSTRUCTION	1/10" Tufted Loop Pile
FIBRE	Stainshield PP
PILE WEIGHT	544g/m ² or 16oz/yd ²
PILE HEIGHT	3.0mm
TOTAL THICKNESS	5.0mm
BACKING	Synth PVC Back™
NO. OF TILES/ BOX	20 pcs / 54sqft (5sqm)




AMAZONESSENTIALS®
carpet tiles

SKYLAR


VIBRANT

Stainshield PP | Synth PVC Back™

PP



SKYLAR | VIBRANT



ES22-08
MEADOW

PRODUCT SPECIFICATION

CONSTRUCTION	1/10" Tufted Loop Pile
FIBRE	Stainshield PP
PILE WEIGHT	544g/m ² or 16oz/yd ²
PILE HEIGHT	3.0mm
TOTAL THICKNESS	5.0mm
BACKING	Synth PVC Back™
NO. OF TILES/ BOX	20 pcs / 54sqft (5sqm)



SKYLAR

VIBRANT

Stainshield PP | Synth PVC Back™

PRODUCT SPECIFICATION

Construction	Tufted Loop Pile
Fiber	Stainshield PP
Gauge	1/10"
Pile Weight	544g/m ² or 16oz/yd ²
Pile Height	3.0mm
Total Thickness	5.0mm
Backing	Synth PVC Back™
Tile Size	50cm x 50cm
Package	20pcs/ctn (5m ²)

ENVIRONMENTAL SPECIFICATION

Total Recycled Content	30% post-consumer recycled material
Indoor Air Quality	CRI Green Label Plus, Greenguard
End-of-life Recycling	Reloop Initiative
Environmental Quality System	ISO14001:2004

PERFORMANCE SPECIFICATION

Flammability	ASTM-D-2859 Pill Test - Result: 8/8
Flooring Radiant Panel	ASTM-E-648-17 - Result: ≥0.87 watts/cm²
Static Propensity	AATCC 134-2011 - Result: Neg. 1.0
Color Fastness	AATCC 165 - Result: 5/5
Stain Resistance	AATCC-175-2003 - Result: 10 - No Residual Stain
Dimensional Stability	Warranted not to change in size by more than 3%
Smoke Density	ASTM E 662-15a - Result: Average 515
Roll Chair	Based on ITTS 0025
Turf Bind	ASTM D 1335 - Result: 6.4 lbs
Piling & Fuzzing	Piling: 5 , Fuzzing: 3



Certified to: Q811 2755:2005
Certification No.: PK011916



Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212

