



**AMAZONESSENTIALS®**  
carpet tiles



**SIRIM**  
Certified to: GB/T 2755 : 2005  
Certification No.: PC011916




**SIRIM**  
ECOLABEL  
Low VOC  
Certified to: SIRIM ECO 035 : 2012  
Certification No.: EL000212

# SKYLAR


## VIBRANT

Stainshield PP | Synth PVC Back™




ES22-11  
**ROSETTE**


### Recommended Laying Patterns



Quarter Turn



Ashlar




Brick

### Product Specification

<b>Fibre</b>	Stainshield PP
<b>Construction</b>	1/10" Tufted Loop Pile
<b>Pile Weight</b>	544g/m <sup>2</sup> or 16oz/yd <sup>2</sup>
<b>Pile Height</b>	3.0mm
<b>Total Thickness</b>	5.0mm
<b>Backing</b>	Synth PVC Back™

### Standard Size






**AMAZONESSENTIALS®**  
carpet tiles

# SKYLAR


VIBRANT

Stainshield PP | Synth PVC Back™

PP



SKYLAR | VIBRANT



ES22-11  
ROSETTE

## PRODUCT SPECIFICATION

<b>CONSTRUCTION</b>	1/10" Tufted Loop Pile
<b>FIBRE</b>	Stainshield PP
<b>PILE WEIGHT</b>	544g/m <sup>2</sup> or 16oz/yd <sup>2</sup>
<b>PILE HEIGHT</b>	3.0mm
<b>TOTAL THICKNESS</b>	5.0mm
<b>BACKING</b>	Synth PVC Back™
<b>NO. OF TILES/ BOX</b>	20 pcs / 54sqft (5sqm)



**AMAZONESSENTIALS®**  
carpet tiles

# SKYLAR


VIBRANT

Stainshield PP | Synth PVC Back™

PP



SKYLAR | VIBRANT



ES22-11  
ROSETTE

## PRODUCT SPECIFICATION

<b>CONSTRUCTION</b>	1/10" Tufted Loop Pile
<b>FIBRE</b>	Stainshield PP
<b>PILE WEIGHT</b>	544g/m <sup>2</sup> or 16oz/yd <sup>2</sup>
<b>PILE HEIGHT</b>	3.0mm
<b>TOTAL THICKNESS</b>	5.0mm
<b>BACKING</b>	Synth PVC Back™
<b>NO. OF TILES/ BOX</b>	20 pcs / 54sqft (5sqm)



# SKYLAR

## VIBRANT

Stainshield PP | Synth PVC Back™

### PRODUCT SPECIFICATION

<b>Construction</b>	Tufted Loop Pile
<b>Fiber</b>	Stainshield PP
<b>Gauge</b>	1/10"
<b>Pile Weight</b>	544g/m <sup>2</sup> or 16oz/yd <sup>2</sup>
<b>Pile Height</b>	3.0mm
<b>Total Thickness</b>	5.0mm
<b>Backing</b>	Synth PVC Back™
<b>Tile Size</b>	50cm x 50cm
<b>Package</b>	20pcs/ctn (5m <sup>2</sup> )

### ENVIRONMENTAL SPECIFICATION

<b>Total Recycled Content</b>	30% post-consumer recycled material
<b>Indoor Air Quality</b>	CRI Green Label Plus, Greenguard
<b>End-of-life Recycling</b>	Reloop Initiative
<b>Environmental Quality System</b>	ISO14001:2004

### PERFORMANCE SPECIFICATION

<b>Flammability</b>	ASTM-D-2859 Pill Test - <b>Result: 8/8</b>
<b>Flooring Radiant Panel</b>	ASTM-E-648-17 - <b>Result: ≥0.87 watts/cm<sup>2</sup></b>
<b>Static Propensity</b>	AATCC 134-2011 - <b>Result: Neg. 1.0</b>
<b>Color Fastness</b>	AATCC 165 - <b>Result: 5/5</b>
<b>Stain Resistance</b>	AATCC-175-2003 - <b>Result: 10 - No Residual Stain</b>
<b>Dimensional Stability</b>	Warranted not to change in size by more than <b>3%</b>
<b>Smoke Density</b>	ASTM E 662-15a - <b>Result: Average 515</b>
<b>Roll Chair</b>	Based on ITTS 0025
<b>Turf Bind</b>	ASTM D 1335 - <b>Result: 6.4 lbs</b>
<b>Piling &amp; Fuzzing</b>	Piling: <b>5</b> , Fuzzing: <b>3</b>



Certified to: Q811 2755:2005  
Certification No.: PK011916



Certified to: SIRIM ECO 035: 2012  
Certification No.: EL000212



PRODUCT CERTIFIED FOR  
ENVIRONMENTAL SENSITIVITIES  
(V.011)



Indoor Air Quality  
Associated Testing Program  
carpet-nub.org

