



**AMAZONESSENTIALS®**  
carpet tiles




**SIRIM**  
Certified to: QBT 2755 : 2005  
Certification No.: PC011916



**SIRIM**  
ECO-LABEL  
Low VOC  
Certified to: SIRIM ECO 035 : 2012  
Certification No.: EL000212

# SHOCKWAVE

MaxLustre PP | Synth PVC Back™



M17-03  
**SHOCKWAVE PEWTER**

## Recommended Laying Patterns




Quarter Turn

## Product Specification

<b>Fibre</b>	MaxLustre PP
<b>Construction</b>	1/12" Multi-Level Loop
<b>Pile Weight</b>	750gm/m <sup>2</sup> or 22oz/yd <sup>2</sup>
<b>Pile Height</b>	2.6mm - 4.5mm (±0.5mm)
<b>Total Thickness</b>	6.5mm (±0.5mm)
<b>Backing</b>	Synth PVC Back™

## Standard Size






**AMAZONESSENTIALS®**  
carpet tiles


# SHOCKWAVE

MaxLustre PP | Synth PVC Back™

PP



SHOCKWAVE




M17-03  
**SHOCKWAVE PEWTER**

## PRODUCT SPECIFICATION

<b>CONSTRUCTION</b>	1/12" Multi-Level Loop
<b>FIBRE</b>	MaxLustre PP
<b>PILE WEIGHT</b>	750gm/m <sup>2</sup> or 22oz/yd <sup>2</sup>
<b>PILE HEIGHT</b>	2.6mm - 4.5mm (±0.5mm)
<b>TOTAL THICKNESS</b>	6.5mm (±0.5mm)
<b>BACKING</b>	Synth PVC Back™
<b>NO. OF TILES/ BOX</b>	20 pcs / 54sqft (5sqm)

PP



M17-03  
**SHOCKWAVE PEWTER**

## PRODUCT SPECIFICATION

<b>CONSTRUCTION</b>	1/12" Multi-Level Loop
<b>FIBRE</b>	MaxLustre PP
<b>PILE WEIGHT</b>	750gm/m <sup>2</sup> or 22oz/yd <sup>2</sup>
<b>PILE HEIGHT</b>	2.6mm - 4.5mm (±0.5mm)
<b>TOTAL THICKNESS</b>	6.5mm (±0.5mm)
<b>BACKING</b>	Synth PVC Back™
<b>NO. OF TILES/ BOX</b>	20 pcs / 54sqft (5sqm)



**AMAZON ESSENTIALS<sup>®</sup>**  
carpet tiles

# SHOCKWAVE

MaxLustre PP | Synth PVC Back™

## PRODUCT SPECIFICATION

Construction	Tufted Textured Loop Pile
Fiber	MaxLustre PP
Gauge	1/12"
Pile Weight	750gm/m <sup>2</sup> or 22oz/yd <sup>2</sup>
Pile Height	2.6mm - 4.5mm (±0.5mm)
Total Thickness	6.5mm (±0.5mm)
Backing	Synth PVC Back™
Tile Size	50cm x 50cm
Package	20pcs / 54sqft (5m <sup>2</sup> )

## ENVIRONMENTAL SPECIFICATION

Sustainability	Production that adheres to ISO14001 & ISO9001 standards
----------------	---

## PERFORMANCE SPECIFICATION

TVOCs	Within CRI limits of less than <b>0.5mg/m<sup>2</sup>/hour</b>
Flammability	Based on ASTM-D-2859 Pill Test - <b>Result: 7/8</b>
Flooring Radiant Panel	Based on ASTM-E-648 - <b>Result: ≥0.45 watts/cm<sup>2</sup></b>
Static Propensity	Permanent Lifetime Protection - less than <b>3.5kv</b>
Electrostatic Propensity	Avg Neg. <b>0.4/0.3 kV</b>
Colour Fastness to Light	Based on AATCC-16E Test - <b>Result: 4/5</b>
Stain Resistance	Based on AATCC-175-1993 - <b>Result: 9 - No Residual Stain</b>
Dimensional Stability	Warranted not to change in size by more that <b>2.4%</b>
Roll Chair	Based on ITTS 205 - <b>Result: 3.0</b>
Tuft Bind	Based on ASTM D 1335 - <b>Result: 8.0 lbs</b>



Certified to: Q811 2755:2005  
Certification No.: PK011916



Certified to: SIRIM ECO 035 : 2012  
Certification No.: EL000212



PRODUCT CERTIFIED FOR  
LOW VOC EMISSIONS  
(VOC)



Indoor Air Quality  
Assessment Institute Program  
carpet-nub.org

