



AMAZONESSENTIALS®
carpet tiles




SIRIM
Certified to: QB/T 2755 : 2005
Certification No.: PC011916



SIRIM
ECO-LABEL
Low VOC
Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212

COSMIC

MaxLustre PP | BioFlex Bitumen Back™



M9016-7
COSMIC BEIGE

Recommended Laying Patterns




Quarter Turn

Product Specification

| | |
|------------------------|--|
| Fibre | MaxLustre PP |
| Construction | 1/12" Multi-Level Loop |
| Pile Weight | 610gm/m ² or 18oz/yd ² |
| Pile Height | 2.5 - 3.5mm |
| Total Thickness | 4.5 - 5.5mm |
| Backing | BioFlex Bitumen Back™ |

Standard Size







AMAZONESSENTIALS®
carpet tiles

COSMIC

MaxLustre PP | BioFlex Bitumen Back™

PP



M9016-7
COSMIC BEIGE

PRODUCT SPECIFICATION

| | |
|--------------------------|--|
| CONSTRUCTION | 1/12" Multi-Level Loop |
| FIBRE | MaxLustre PP |
| PILE WEIGHT | 610gm/m ² or 18oz/yd ² |
| PILE HEIGHT | 2.5 - 3.5mm |
| TOTAL THICKNESS | 4.5 - 5.5mm |
| BACKING | BioFlex Bitumen Back™ |
| NO. OF TILES/ BOX | 20 pcs / 54sqft (5sqm) |



COSMIC

MaxLustre PP | BioFlex Bitumen Back™

PRODUCT SPECIFICATION

| | |
|------------------------|--|
| Construction | Multi-level Loop |
| Fiber | MaxLustre PP |
| Gauge | 1/12" |
| Pile Weight | 610gm/m ² or 18oz/yd ² |
| Pile Height | 2.5 - 3.5mm |
| Total Thickness | 4.5 - 5.5mm |
| Backing | BioFlex Bitumen Back™ |
| Tile Size | 50cm x 50cm |
| Package | 20pcs / 54sqft (5m ²) |

ENVIRONMENTAL SPECIFICATION

| | |
|-----------------------|--|
| Sustainability | Production that adheres to ISO14001 and ISO9001 with all yarns used are Solution dyed to minimize use of water and exclude any effluent. |
|-----------------------|--|

PERFORMANCE SPECIFICATION

| | |
|----------------------------------|--|
| Static Electricity | Permanent lifetime protection - less than 3.5kV |
| Lodging-Resistance | Superior fibre resistance |
| Wear Warranty | Warranted not to lose more than 15% pile fibre by weight under normal commercial use within 15 years |
| Dimensional Stability | Warranted not to change in size by more than 0.5mm, as well as resistant to doming and dishing under normal use. |
| Color Fastness to Rubbing | GB/T3920-2008 Standard: >Grade 4 for dry rubbing >Grade 3 for wet rubbing |



Certified to: QB1 2735:2005
Certification No.: PK011916



Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212



PRODUCT CERTIFIED FOR
ENVIRONMENTAL PERFORMANCE
(UL GREENGUARD)



Indoor Air Quality
Advanced Testing Program
carpet-nub.org

