



AMAZONPRIMO[®]
contract carpet tiles



Certified to: GB/T 2755 : 2005
Certification No.: PC011916



Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212


LAZIO

100% Resilia Nylon 6 | Synth PVC Back™




P8002-5
LAZIO NAVY


Recommended Laying Patterns



Quarter Turn



Ashlar




Brick


Product Specification

Fibre 100% Resilia Nylon 6
Construction 1/12" Multi-Level Loop
Pile Weight 610gm/m² or 18oz/yd²
Pile Height 2.5 - 3.5mm
Total Thickness 5.0 - 6.0mm
Backing Synth PVC Back™



Standard Size



NY



Quarter Turn



P8002-5
LAZIO NAVY

PRODUCT SPECIFICATION

CONSTRUCTION	1/12" Multi-Level Loop
FIBRE	100% Resilia Nylon 6
PILE WEIGHT	610gm/m ² or 18oz/yd ²
PILE HEIGHT	2.5 - 3.5mm
TOTAL THICKNESS	5.0 - 6.0mm
BACKING	Synth PVC Back™
NO. OF TILES/ BOX	20 pcs / 54sqft (5sqm)




AMAZONPRIMO[®]
contract carpet tiles


LAZIO

100% Resilia Nylon 6 | Synth PVC Back™

NY



LAZIO



P8002-5
LAZIO NAVY

PRODUCT SPECIFICATION

CONSTRUCTION	1/12" Multi-Level Loop
FIBRE	100% Resilia Nylon 6
PILE WEIGHT	610gm/m ² or 18oz/yd ²
PILE HEIGHT	2.5 - 3.5mm
TOTAL THICKNESS	5.0 - 6.0mm
BACKING	Synth PVC Back™
NO. OF TILES/ BOX	20 pcs / 54sqft (5sqm)



AMAZONPRIMO[®]
contract carpet tiles

LAZIO

100% Resilia Nylon 6 | Synth PVC Back™

PRODUCT SPECIFICATION

Construction	Multi-level Loop
Fiber	100% Resilia Nylon 6
Gauge	1/12"
Pile Weight	610gm/m ² or 18oz/yd ²
Pile Height	2.5 - 3.5mm
Total Thickness	5.0 - 6.0mm
Backing	Synth PVC Back™
Tile Size	50cm x 50cm
Package	20pcs / 54sqft (5m ²)

ENVIRONMENTAL SPECIFICATION

Sustainability	Production that adheres to ISO14001 and ISO9001 with all yarns used are Solution dyed to minimize use of water and exclude any effluent.
-----------------------	--

PERFORMANCE SPECIFICATION

Flammability	Pass GB 8624-2012 Pass GB/T 14768-93
Static Electricity	Pass AATCC-134 Pass GB/T 18044-2000
Smoke Density	Pass ASTM-E-662 < =450 DMC Pass GB/T 8624-2012
Color Fastness	Pass AATCC-165
Tensile Strength Test	Pass ISO13934-1 Warp 3112.9
Antimicrobial	Pass AATCC TM 174



Certified to: Q81 2735:2005
Certification No.: PK011916



Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212



PRODUCT CERTIFIED FOR
LOW VOC EMISSIONS
(VOC)



Indoor Air Quality
Associated Society Program
carpet-nab.org



RESILIA
NYLON