



AMAZONPRIMO[®]
contract carpet tiles




SIRIM
Certified to : GB/T 2755 : 2005
Certification No. : PC011916



SIRIM
ECOLABEL
Low VOC
Certified to : SIRIM ECO 035 : 2012
Certification No. : EL000212


RISE & SHINE

100% Resilia Nylon 6 | Synth PVC Back™




P8005-8
SHINE SAGE


Recommended Laying Patterns



Quarter Turn



Ashlar




Brick


Product Specification

| | |
|------------------------|--|
| Fibre | 100% Resilia Nylon 6 |
| Construction | 1/12" Multi-Level Loop |
| Pile Weight | 750gm/m ² or 22oz/yd ² |
| Pile Height | 3.0 - 5.5mm |
| Total Thickness | 5.0 - 6.0mm |
| Backing | Synth PVC Back™ |

Standard Size




NY



Quarter Turn



RISE & SHINE



P8005-08
SHINE SAGE

PRODUCT SPECIFICATION

| | |
|--------------------------|--|
| CONSTRUCTION | 1/12" Multi-Level Loop |
| FIBRE | 100% Resilia Nylon 6 |
| PILE WEIGHT | 750gm/m ² or 22oz/yd ² |
| PILE HEIGHT | 3.0 - 5.5mm |
| TOTAL THICKNESS | 5.0 - 6.0mm |
| BACKING | Synth PVC Back™ |
| NO. OF TILES/ BOX | 20 pcs / 54sqft (5sqm) |



AMAZONPRIMO[®]
contract carpet tiles


RISE & SHINE

100% Resilia Nylon 6 | Synth PVC Back™

NY



RISE & SHINE



P8005-08
SHINE SAGE

PRODUCT SPECIFICATION

| | |
|--------------------------|--|
| CONSTRUCTION | 1/12" Multi-Level Loop |
| FIBRE | 100% Resilia Nylon 6 |
| PILE WEIGHT | 750gm/m ² or 22oz/yd ² |
| PILE HEIGHT | 3.0 - 5.5mm |
| TOTAL THICKNESS | 5.0 - 6.0mm |
| BACKING | Synth PVC Back™ |
| NO. OF TILES/ BOX | 20 pcs / 54sqft (5sqm) |



AMAZONPRIMO[®]
contract carpet tiles

RISE & SHINE

100% Resilia Nylon 6 | Synth PVC Back™

PRODUCT SPECIFICATION

| | |
|------------------------|--|
| Construction | Multi-level Loop |
| Fiber | 100% Resilia Nylon 6 |
| Gauge | 1/12" |
| Pile Weight | 750gm/m ² or 22oz/yd ² |
| Pile Height | 3.0 - 5.5mm |
| Total Thickness | 5.0 - 6.0mm |
| Backing | Synth PVC Back™ |
| Tile Size | 50cm x 50cm |
| Package | 20pcs / 54sqft (5m ²) |

ENVIRONMENTAL SPECIFICATION

| | |
|-----------------------|--|
| Sustainability | Production that adheres to ISO14001 and ISO9001 with all yarns used are Solution dyed to minimize use of water and exclude any effluent. |
|-----------------------|--|

PERFORMANCE SPECIFICATION

| | |
|------------------------------|---|
| Flammability | Pass GB 8624-2012 Pass GB/T 14768-93 |
| Static Electricity | Pass AATCC-134 Pass GB/T 18044-2000 |
| Smoke Density | Pass ASTM-E-662 < =450 DMC Pass GB/T 8624-2012 |
| Color Fastness | Pass AATCC-165 |
| Tensile Strength Test | Pass ISO13934-1 Warp 3112.9 |
| Antimicrobial | Pass AATCC TM 174 |



Certified to: QB1 2735-2005
Certification No.: PK011916



Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212



PRODUCT CERTIFIED FOR
ENVIRONMENTAL SENSITIVE
USGBC/CES
GREENGUARD
UL 2898



GREEN LABEL
+PLUS
Indoor Air Quality
Associated Testing Program
CRI 1001-1001-010



RESILIA
NYLON