



AMAZONPRIMO[®]
contract carpet tiles




SIRIM
Certified to: GB/T 2755 : 2005
Certification No.: PC011916



SIRIM
ECO-LABEL
Low VOC
Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212


FAZE & MAZE

100% Resilia Nylon 6 Air Entangled | Synth PVC Back™




P8008-2
FAZE ASH


Recommended Laying Patterns



Quarter Turn



Ashlar




Brick

Product Specification

| | |
|------------------------|--|
| Fibre | 100% Resilia Nylon 6 Air Entangled |
| Construction | 1/12" Multi-Level Loop |
| Pile Weight | 710gm/m ² or 21oz/yd ² |
| Pile Height | 3.0 - 4.0mm |
| Total Thickness | 5.0 - 6.0mm |
| Backing | Synth PVC Back™ |

Standard Size






AMAZONPRIMO®
contract carpet tiles


FAZE & MAZE

100% Resilia Nylon 6 Air Entangled | Synth PVC Back™

NY



FAZE & MAZE



P8008-2
FAZE ASH

PRODUCT SPECIFICATION

| | |
|--------------------------|--|
| CONSTRUCTION | 1/12" Multi-Level Loop |
| FIBRE | 100% Resilia Nylon 6 Air Entangled |
| PILE WEIGHT | 710gm/m ² or 21oz/yd ² |
| PILE HEIGHT | 3.0 - 4.0mm |
| TOTAL THICKNESS | 5.0 - 6.0mm |
| BACKING | Synth PVC Back™ |
| NO. OF TILES/ BOX | 20 pcs / 54sqft (5sqm) |



AMAZONPRIMO[®]
contract carpet tiles

FAZE & MAZE

100% Resilia Nylon 6 Air Entangled | Synth PVC Back™

PRODUCT SPECIFICATION

| | |
|------------------------|--|
| Construction | Multi-level Loop |
| Fiber | 100% Resilia Nylon 6 Air Entangled |
| Gauge | 1/12" |
| Pile Weight | 710gm/m ² or 21oz/yd ² |
| Pile Height | 3.0 - 4.0mm |
| Total Thickness | 5.0 - 6.0mm |
| Backing | Synth PVC Back™ |
| Tile Size | 50cm x 50cm |
| Package | 20pcs / 54sqft (5m ²) |

ENVIRONMENTAL SPECIFICATION

| | |
|-----------------------|--|
| Sustainability | Production that adheres to ISO14001 and ISO9001 with all yarns used are Solution dyed to minimize use of water and exclude any effluent. |
|-----------------------|--|

PERFORMANCE SPECIFICATION

| | |
|----------------------------------|--|
| Static Electricity | Permanent lifetime protection - less than 3.5kV |
| Lodging-Resistance | Superior fibre resistance |
| Wear Warranty | Warranted not to lose more than 15% pile fibre by weight under normal commercial use within 15 years |
| Dimensional Stability | Warranted not to change in size by more than 0.5mm, as well as resistant to doming and dishing under normal use. |
| Color Fastness to Rubbing | GB/T3920-2008 Standard: >Grade 4 for dry rubbing >Grade 3 for wet rubbing |



Certified to: Q81 2755:2005
Certification No.: PK011916



Certified to: SIRIM ECO 035 : 2012
Certification No.: EL000212



PRODUCT CERTIFIED FOR
LOWER VOC EMISSIONS
(0.05)



Indoor Air Quality
Associated Testing Program
carpet-nab.org



RESILIA
NYLON